




DASAR@ 270

Outdoor LED inground fitting, 4000K, round, IP67, asymmetrical beam

The IP 65 / IP 67 safety class does not only mean that the DASAR@ 270 inground fitting is only protected from dust, but also from penetration by water, even if it is occasionally submerged in water. With its asymmetric light distribution, the DASAR@ 270 is an excellent companion for your open spaces or your pond in the garden. Are you looking for amazing light for your outdoor area? This is what you get with the fixed Premium LED of the DASAR@ 270 inground fitting. By choosing our DASAR@ 270, you are also choosing quality, innovation and fair prices. This has characterised SLV GmbH for almost 40 years.



TECHNICAL DATA

Item no.:	1002895
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	700 mA/V
Height	20.3 cm
Diameter	27.0 cm
Installation diameter	25.0 cm
Installation depth	19.9 cm
Net weight	5.206 kg
Gross weight	5.975 kg
IP Code	IP 65 / IP 67
Safety class	I
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Number of through-wires	60
Wattage	30.0 W
Lumen	2100 lm
Colour temperature	4000 Kelvin
CRI	>80
Binning	3
LXXBXX data	L70B50



Service life	50000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Mechanical loading	2 t
BIG WHITE Page	733

Notes
