


# SolarEye®80»

## Product Range

- **LED signal:** Steady or slow flash
- **Standard products:** White steady, Red flash and Bat Hat
- **Special colours to order:** Yellow, Green and Blue steady or flash, Red steady and White flash
- **Supplied in a box of 20:** Weight 5.5kg

## Technical Characteristics

- **Material:** High impact durable engineering grade polymer
- **Light source:** LED (100,000hrs life)
- **Battery:** Long life LFP type battery (8yrs+ anticipated)
- **Working temperature:** -20c to +70c
- **Body dimensions:** 80mm Diameter
- **Installed height:** 6mm Nominal
- **Milling depth:** 30mm
- **Weight:** 275g
- **Fixing adhesive:** 2 component moisture tolerant epoxy
- **Working time after full charge:** Flashing 400hrs+ steady 200hrs+
- **Flash rate:** 1 Sec on, 1 sec off
- **Waterproof quality:** IP68
- **High Visibility:** Up to 500m



## Installation & Product FAQ's

- Simple installation equipment, 2 persons required for larger jobs
- Dry cut using a milling tool
- Up to 200 pieces per day can be installed
- Adhesive takes 30mins to cure so minimal disruption
- Auto on/off light sensor
- Suitable for low traffic roads i.e: golf clubs, holiday villages & car parks

Call us for specific advice on positioning and installation methods for the SolarEye®80.